


**50 AC - ACCESSORI DI FISSAGGIO**

**SUPPORTI**

**INSTALLAZIONE**

min  
-5°C



max  
+60°C

**GWT 750°C**



EN 60695-2-11

GW50601



**SUPPORTI A SCATTO IN POLIMERO ANTIURTO - GRIGIO RAL 7035**

Codice	Per tubi Ø esterno (mm)	Dist. muro asse tubo mm	Caratteristiche	Conf. Imb.	Prezzo EURO cadauno
GW 50 601	16	20	Halogen free	100/1800	13,20 **
GW 50 602	20	22	Halogen free	100/1600	15,20 **
GW 50 603	25	24.5	Halogen free	100/900	16,80 **
GW 50 604	32	28	Halogen free	100/900	26,10 **
GW 50 628	40	32		50/450	40,90 **
GW 50 629	50	37		50/450	51,10 **

NOTA: adatti per chiodatrici automatiche.  
Halogen free secondo la norma EN 50267-2-2.

GW50605



**SUPPORTI A COLLARE IN POLIMERO ANTIURTO - GRIGIO RAL 7035**

Codice	Per tubi Ø esterno (mm)	Dist. muro asse tubo mm	Caratteristiche	Conf. Imb.	Prezzo EURO cadauno
GW 50 605	16	20	Halogen free	100/900	14,30 **
GW 50 606	20	22	Halogen free	100/900	15,80 **
GW 50 607	25	24.5	Halogen free	100/600	17,60 **
GW 50 608	32	28	Halogen free	50/450	27,60 **
GW 50 630	40	32	Halogen free	35/350	43,90 **
GW 50 631	50	37	Halogen free	25/200	52,80 **

NOTA: Halogen free secondo la norma EN 50267-2-2.

GW50609



**GUIDA COMPONIBILE AD INCASTRO PER FISSAGGIO SUPPORTI IN POLIMERO ANTIURTO - GRIGIO RAL 7035**

Codice	Lunghezza (mm)	Dist. muro asse tubo mm	Conf. Imb.	Prezzo EURO cadauno
GW 50 609	200	6	50/350	47,00 **